

TITLE
BASE OF SURFACE MOUNTED INDUCTOR

5

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a base of inductor, and
10 more particularly to a base of surface mounted inductor.

2. Description of the Prior Art

Generally, the conventional inductor fails to serve as a
15 surface mounted device (SMD) due to the pin-shaped terminals
of the coil. A base having strips of stem is required to
transform the conventional inductor into a surface mounted
device. As shown in Fig.1, the conventional base 20 includes
an upper surface and a flat bottom surface (not shown). The
20 upper surface further includes a cavity 21 and two U-shaped
metal parts 30 formed on the periphery of the cavity. Each of
the metal parts 30 is embedded into the periphery of the base
20 and provides a lower surface to electrically contact with
the board.

25

Still referring to Fig.1, to transform the conventional
inductor into a surface mounted inductor 70, the core 11 of the
inductor is partially positioned in the cavity 21. Then, a
conductive line is wound around the core 11 to form the coil
30 12. Finally, the pin-shaped terminals of the coil 12 are
connected with the metal parts 30, i.e. by welding. After that,
the conventional inductor can serve as a surface mounted
inductor.

However, the conventional base exhibits the following disadvantages. First, the bottom surface of the conventional surface mounted inductor 70 fails to provide satisfying flatness since the U-shaped metal parts 30 are partially embedded into the base 20. Using welding to connect the coil 12 with the metal parts 30 consumes power and may cause danger. The terminals of the coil originally connecting with the metal parts 30 tend to loosen. The base 20 is made of plastic and thus fragile if the thickness is not enough. However, during trying to increase the thickness to enhance the strength, the profile of the base is inevitably increased. The shape of the conventional surface mounted inductor 70 is symmetrical and the apparatus fails to automatically identify the direction of the magnetic field during using. Therefore, it is confusing and inconvenient. The conventional surface mounted inductor needs additional identification mark, such as the dots 60.

Accordingly, there has been a strongly felt need for a novel base for improving the disadvantages described above.

SUMMARY OF THE INVENTION

Consideration of the disadvantages of the conventional base described above, the main object of the present invention is to provide an improved base can overcome the aforementioned problems.

The present invention discloses a base for transforming an inductor into a surface mounted device. The present inductor includes a core and a coil wound around the core and having two pin-shaped terminals. The base further includes an insulating element (i.e. plastic), a first conductive element and a second conductive element. The insulating element further includes an upper surface having a cavity and a flat bottom surface.

The first conductive element and the second conductive element substantially are Z-shaped and have a strip of first stem and the second stem, respectively. The insulating element exposes the first stem and the portion of the lower surface of the first conductive element. The remaining portion of the first conductive element is embedded into the insulating element. The insulating element exposes the second stem and the portion of the lower surface of the second conductive element. The remaining portion of the second conductive element is embedded into the insulating element. Besides, the exposed lower surface of the first conductive element, the exposed lower surface of the second conductive element and the bottom surface of the base are arranged on the same level. Moreover, one section of the first conductive element extends toward the second stem and further crosses the virtual second cross-sectional line.

According to the present invention, the core is partially positioned on the first cavity of the base. In addition, the pin-shaped terminals of the coil are further wound around the stems and so as to form combination. In this manner, the inductor is transformed into a surface mounted inductor by means of the base.

Compared to prior art, the present invention at least exhibits the advantages described as follows. The bottom surface of the present surface mounted inductor provides satisfying flatness since the exposed lower surface of the first conductive element, the exposed lower surface of the second conductive element and the bottom surface of the base are arranged on the same level. The terminals of the coil are wound around the conductive elements such that the consumed power for welding is not required. The terminals of the coil wound around the recessed edges of the stems are fixed properly. Since the Z-shaped first and second conductive elements are partially

embedded into the insulating element, the rigidity of the
insulating element is enhanced. Alternatively, the insulating
element can be decreased meanwhile keeping the rigidity. The
shape of the present surface mounted inductor is unsymmetrical
and the direction of the magnetic field can be automatically
identified during using. That is, the additional
identification mark can be omitted.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing aspects and many of the attendant advantages
of this invention will become more readily appreciated as the
same becomes better understood by reference to the following
detailed description, when taken in conjunction with the
accompanying drawings, wherein:

Fig.1 depicts a conventional base used in a surface mounted
inductor;

Fig.2 depicts the base having the inductor formed thereon
according to the present invention;

Fig.3(a) depicts the exploded view illustrating the base
according to the present invention;

Fig.3(b) depicts the top plan view illustrating the base
according to the present invention;

Fig.4(a) depicts the side view illustrating the base
according to the present invention; and

Fig.4(b) depicts the partially amplified side view
illustrating the base according to the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

The present invention discloses a base 200 for transforming
5 an inductor into a surface mounted device. As shown in Fig.2,
the present inductor 100 includes a core 110 and a coil 120.
The coil 120 is wound around the core 110 and thus has two
pin-shaped terminals 125. The base 200 includes an upper
surface having a first cavity 210 and strips of stems 550 and
10 650. The first cavity 210 accommodates a part of the inductor
100 (i.e. the bottom surface of the core 110). Besides, the
pin-shaped terminals 125 are further wound around the stems 550
and 650 so as to form combination. In this manner, the inductor
is transformed into a surface mounted inductor 700 by means of
15 the base 200.

Referring to Fig.2 and Fig.3(a), the base 200 further
includes an insulating element 300, a first conductive element
500 and a second conductive element 600. The insulating element
20 300 further includes an upper surface and a flat bottom surface
(not shown). As described above, the upper surface has a first
cavity 210 accommodating the bottom surface of the core 110 of
the inductor 100. Among these, the bottom surface of the base
200 is flat and attached to a board (not shown) during using.

Referring to Fig.3(b), the first conductive element 500
further includes a first section 510, a second section 520 and
a first bend section 530. The second conductive element 600
further includes a third section 610, a fourth section 620 and
30 a second bend section 630. Among these, the first section 510,
the first bend section 530, the third section 610 and the second
bend section 630 is embedded into (i.e. by molding) the
insulating element 300. The second section 520 and the fourth
section 620 are formed on the periphery of the insulating
35 element 300. Additionally, the second section 520 and the

fourth section 620 further include a strip of first stem 550 and a second stem 650, respectively. The insulating element 300 exposes the first stem 550 and the second stem 650. The insulating element 300 also exposes the lower surfaces of the second section 520 and the fourth section 620, explained in greater detail below. That is, the second section 520 and the fourth section 620 are partially embedded into the insulating element 300.

Still referring to Fig.3(b), note that the base 200 is unsymmetrical based on a view along the first cross-sectional line, such as the horizontal cross-sectional line AA' passing through the center of the base 200. To expose the first stem 550 and the second stem 650, the upper portion and the lower portion of the insulating element 300 separated by the cross-sectional line AA' are unsymmetrical to each other. Among these, the exposed first stem 550 and the second stem 650 are located on the lower portion. Therefore, according to the present invention, the desired direction of the magnetic field can be previously determined automatically, rather than manually, during assembling. Besides, the present invention can be packaged in a tape reel and meanwhile oriented toward the same direction by a suitable container matching the shape of the present inductor formed on the tape reel. Because the present inductor fails to be packaged in the tape reel if an incorrect orientation is given. Contrary to the present invention, it is unable to identify the desired direction of the magnetic field of the conventional inductor automatically during assembling since the conventional inductor is symmetrical. In this case, the desired orientations of the conventional inductors packaged in a tape reel tend to be confused, which cause inconvenience. For example, the desired direction of the magnetic field of the conventional inductors packaged in a tape reel may be oriented toward the different directions. The above-mentioned first cross-sectional line

may be a virtual line extending from the second section 520 to the fourth section 620. Besides, the first cross-sectional line is perpendicular to the second cross-sectional line, such as the cross-sectional line BB' shown in Fig.3(b). The second cross-sectional line extends from the first section 510 to the third section 610. Besides, the two portions of the insulating element 300 separated by the second cross-sectional line, such as the right portion and the left portion, are mirror symmetrical.

Still referring to Fig.3(b), the first stem 550 further includes at least one recessed edge 555. The second stem 650 further includes at least one recessed edge 655. As described above, the terminals of the coil of the inductor 100 shown in Fig.2 are further wound around the recessed edges 555 of the first stem 550 and the recessed edges 655 of the second stem 650, thereby enhancing the combination. Even though the first stem 550 and the second stem 650 are bent, the terminals of the coil wound around the first stem 550 and the second stem 650 will not loosen. Therefore, according to the present invention, combining the terminals of the coil with the first stem 550 and the second stem 650 does not require welding.

Still referring to Fig.3(b), in the first conductive element 500, the first section 510 connects with the second section 520 through the first bend section 530. Similarly, in the second conductive element 600, the third section 610 connects with the fourth section 620 through the second bend section 630. Therefore, as the top plan view shown in Fig.3(b), the first conductive element 500 and the second conductive element 600 substantially are Z-shaped. Moreover, the third section 610 extends toward the first stem 550 and further crosses the second cross-sectional line BB'. The first section 510 extends toward the fourth section 620 and further crosses the second cross-sectional line BB'. As such, the first section

510 and the third section 610 enable the base 200 to resist the bending force along or parallel to the second cross-sectional line, such as the cross-sectional line BB'. Alternatively, the strength of the base 200 is enhanced enough and meanwhile the profile of the insulating element is thus reduced.

Refer to Fig.4(a) showing the side view illustrating the first conductive element 500 and the second conductive element 600. Obviously, as shown in the dotted line, there is a drop formed between the first bend section 530 and the second section 520. Besides, there is also a drop formed between the second bend section 630 and the fourth section 620. Alternatively, the level of the second section 520 is lower than the level of the first bend section 530. Besides, the insulating element 300 exposes the lower surface of the second section 520. Similarly, the level of the fourth section 620 is lower than the level of the second section 630. The insulating element 300 exposes the lower surface of the fourth section 620. Note that the lower surface of the second section 520, the lower surface of the fourth section 620 and the bottom surface of the base 200 are arranged on the same level. As such, the second section 520 and the fourth section 620 electrically contact the board having the base 200 mounted thereon. Therefore, the first section 510 and the third section 610 are far away from the board and form isolation therebetween.

Referring to Fig.3(b) and Fig.4(b) which shows the partially amplified side view illustrating the first or second conductive element, there is at least one second cavity 570 formed on the upper surfaces and the lower surfaces of the first conductive element 500 and the second conductive element 600, respectively. The second cavity 570 enables the clamp holder 800 to clamp the first conductive element 500 or the second conductive element 600 during molding. As such, the first conductive element 500 and the second conductive element 600

can resist the impact and thus be fixed properly during molding.
The clamp holder 800 is removed after molding.

As is understood by a person skilled in the art, the
5 foregoing preferred embodiments of the present invention are
illustrated of the present invention rather than limiting of
the present invention. It is intended to cover various
modifications and similar arrangements included within the
spirit and scope of the appended claims, the scope of which
10 should be accorded the broadest interpretation so as to
encompass all such modifications and similar structure.